



**Honda CBR600RR (07-12) Frame Slider
Installation Instructions
Part Numbers: 750-3320, 750-3329, 750-3349,
750-3340, 755-3349 & 850-3340**

MADE IN THE USA!

Carefully read instructions in their entirety before the install

Professional installation is recommended. Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from factory service manual, safety goggles and gloves. The motorcycle must be in a fixed secure position before the install process begins. **DO NOT** remove both engine studs at the same time. **Shogun is not responsible for any part of your motorcycle for any reason.** Precisely measure location of cut and if in doubt at any point please call us before the install process has begun.

Replacement Parts List: Left Side Components (as if you were sitting on the bike)

QTY	Price each	Part Numbers	Descriptions
1	\$20.00	99-FS-750-3329-L	Black Left Side Puck
1	\$20.00	99-FS-750-3320-L	White Left Side Puck
1	\$25.00	99-FS-850-3320-L	Chrome Left Side Puck
1	\$5.50	99-HB-SH12125090	Socket Cap 12 X 1.25 X 90 Main Engine Stud

Replacement Parts List: Right Side Components (as if you were sitting on the bike)

1	\$20.00	99-FS-750-3329-R	Black Right Side Puck
1	\$20.00	99-FS-750-3320-R	White Right Side Puck
1	\$25.00	99-FS-850-3320-R	Chrome Right Side Puck
1	\$5.50	99-HB-SH12125090	Socket Cap 12 X 1.25 X 90 Main Engine Stud

Frame Sliders: Left longer than right, bolts same left and right 12 X 1.25 X 90mm.

Installation Steps apply to left and right hand side.

1. Some photos in this section are used for **illustration** examples only. It is up to you how you decide to cut your motorcycle's bodywork to accept the frame slider; there are many different ways customers go through this process. **Shogun is not responsible for any part of your motorcycle for any reason.** Precisely measure location of cut and if in doubt at any point please call us before the install process has begun. **Professional installation is recommended.** Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from factory service manual, **safety goggles and gloves.**
2. Locating and cutting the body. This is a simple illustration of how most of us install the product here. It takes a bit longer but our end results have been more consistent with a better overall fit and finish. We start with (99-SPOT-1212560) Shogun Spot tool. It's nothing special just a 12mm socket cap bolt with a 1.25 pitch that we cut the head off of and sharpen to a point. You can purchase the tool for \$12.99 or go to your local hardware store and make your own. Keep in

mind Metric 10 or 12mm X 1.25 pitch bolts (most common sportbike engine studs) are fairly hard to find. Make sure you know the size and that the bolt you're buying is a 1.25 pitch bolt.



With the body removed, thread in by hand your spot tool. Make sure you have the spot tool screwed in enough to clear the body on the inside.


3. Loosely mount your bodywork and adjust the spot tool out to lightly touch the inside of the body. **Make sure you have at least 15mm of thread engagement, without that the spot tool will tend to sag down giving you a false location.** With the body mounted in the correct location and softly tap or press with palm to leave a spot mark on the inside of the body. Be careful not to scratch or chip the body.





Apply pressure with your palm
to create a pressure point.


4. Remove the bodywork and double check location of spot mark the tool has created.




5. Body Prep. Use masking tape to completely mask off the area on the body where you will be working. We usually will tape off approximately 6 to 8 inches around the though hole area and any other edges that could get bumped or scratched while working. Tip: In some locations you may want to double up the thickness of the masking take to give extra protection.




- Using a small drill 1/8 inch or so drill a pilot hole in the body(see above photo). Remount bodywork and double check the hole location with the spot tool still inserted (arrow in picture below is pointing to spot tool). With pilot hole cut and on center, remove body panel to prep for cutting.



- A pencil was then used to draw our diameter of desired shaped hole using a compass tool. A flexible hole template can also be used for the same purpose. Place the hole template on center of the pilot hole (or spot tool) and draw your desired diameter.



- For this application we used a step drill to open the hole big enough for a dremel tool with a sanding roll and opened up the hole little by little. **MAKE SURE YOU WEAR PROTECTIVE GOGGLES AND GLOVES** As you cut and open the hole to your scribe marks keep checking that the hole is lining up with your puck dimensions or the spot tool. If for some reason you cut too big and you want to close the gap around the puck we use windscreen trim or window seal with 3m adhesive. Trim the seal to fit the hole and get the seam to meet under the puck so it is less visible. (window seal usually found at most hardware stores)



- Mount body then slider then torque down to OEM specs. Remember each side was done the same way.



READ CAREFULLY

Shogun cannot guarantee that they will protect your motorcycle from any extent of damage. Shogun frame sliders are really meant to help possibly save the frame from damage in the event of a crash. Because Shogun frame slider products have been successful in saving cases, bodywork, levers and so on in the past, customers just assume sometimes you can put the product on and no damage will happen. The fact is, some crashes result in little or no damage to the motorcycle and some bikes are destroyed. It's kind of like a bumper on a car sometimes it works sometimes it doesn't, it really depends on all the different forces applied during the incident. We've seen bikes crash at 100 mph with little damage and some at 15 mph with major damage.