



6240 Box Springs Blvd., Unit E
Riverside, CA 92507
web: <http://www.imsproducts.com>
Orders: (800) 237-9906
Information: (951) 653-7720
FAX: (951) 653-1060

IMS
FUEL TANK:
KAWASAKI:
2.7 Gallon

KXF250 (06-08') : KX-32
IMS Part #:
113147 / 213147

IMS
FUEL TANK:
KAWASAKI:
2.9 Gallon

KXF450 (06-07') : KX-34
IMS Part #:
113149 / 213149

PARTS LIST

- (1) Fuel Tank
 - (1)*Gas Cap & Seal
 - (1) Petcock Gasket
 - (1) "CR-2000" Front Mount Bracket
 - (2) 6mm x 12mm , Large Flange bolts
 - (1) 4 1/2" Fuel Line
 - (2) Hose Clamps
- *Excluded on Dry-Break Series**

STOCK ITEMS TO USE

- Petcock & Screws
- Seat Hook Assembly
- Rear Strap Screw

WARNING!

Clean Tank Interior Thoroughly Before Installation. Install This Fuel Tank ONLY In a Well Ventilated Area, As Gasoline Fumes Are EXTREMELY Dangerous. DO NOT START OR OPERATE THE VEHICLE IF THERE ARE ANY FUEL LEAKS! IMS Recommends That Installation Be Done By a Licensed Mechanic. Read All Instructions First Before Beginning Installation.

TANK REMOVAL

Drain all fuel from OEM fuel tank into a government approved fuel container with a greater capacity than OEM fuel tank on vehicle.

The stock fuel lines, petcock, radiator shrouds (some models) & seat need to be removed. When removing any tank mount brackets be sure to note the **RIGHT & LEFT SIDE** brackets. They must be installed on the appropriate side for the tank to mount properly.

TANK INSTALLATION

Transfer the following items to IMS fuel tank, seat hook assembly, rear strap screw, and petcock using rubber petcock gasket provided.

Find the front mount assembly provided. Insert the OEM screw provided thru OEM washer, front mount bracket. Install tank onto frame. Adjust front mount to best fitment position. Remove tank, tighten mount bolt. Replace tank onto frame. Fasten mount to tank with 6mm x 12mm bolts. Attach rear hold down strap and replace seat.

Be sure that the IMS fuel tank is mounted securely & doesn't bind or in any way inhibit the function of the motorcycle or the rider's movement.

Ensure that there is no sharp objects, (handle bars, tank mounting bolts, seat bolts etc.) that rub against the tank, they may eventually puncture the tank.

Connect the fuel line & turn the petcock to the closed position, replace the seat & shrouds if necessary, check for any leaks & enjoy your longer ride!