

MOUNTING SUGGESTIONS:

Harley-Davidson[®] Softail Deluxe FLSTN 2005-16

Solo and Passenger Seat

Hardware: Solo seat:

Small retaining washers

X 2

Passenger seat:

1⁄4"-20 x 1" Allen bolt

1/4" chrome washer Stock hardware for

mounting chrome rail

Tools needed: Phillips screwdriver

½" hex wrench

Two ³/₈" hex wrenches

T30 Torx wrench 5/32" Allen wrench

Note: These seats are designed to be used with the standard Deluxe rack. They are not intended for use with the CVO rack or with no rack at all.

Removal of Stock Seat:

1. Remove the rear 1/4"-20 screw from behind the passenger seat with a Phillips screwdriver. Slide the passenger seat up and back to remove from the motorcycle.



2. Remove the threaded spacer and washer from the rear mount hole on the rack using a ½" hex wrench. (This spacer will not be used to mount the Mustang passenger seat.)

3. Remove the two stock slotted nuts from behind the solo, and lift the solo up and back to remove from the motorcycle.



4. Using two 3/8" hex wrenches, loosen the nuts holding the sides of the chrome rail to the stock solo. Using a T30 Torx wrench, remove the central rear bolt which connects the solo's rear bracket to the chrome rail. Carefully disengage the chrome rail from the stock solo.

Installation of Mustang Seat:



1. Remove one of the large retaining washers from the fender studs and replace with the supplied small retaining washer. Repeat for other stud.

Note: Do not remove both retaining washers at the same time!

- 2. Mount the chrome rail to the Mustang solo using stock hardware.
- 3. Insert the Mustang solo's front bracket into the frame receiver below the fuel tank. Align the rear chrome brackets with the fender studs and secure to fender using the stock slotted nuts.
- 4. Slide the passenger seat forward so the seat's front brackets engage the slots in the fender nuts.
- 5. Using the supplied $\frac{1}{4}$ "-20 x 1" Allen bolt and chrome washer, secure the passenger seat's rear bracket to the rack and fender with a $\frac{5}{32}$ " Allen wrench.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76231, 76232, 76235, 76236, 79913, 79914

You are cordially invited to Tour the Mustang Factory

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.

